

Perfect Protection

Locpro

Smart Easy Premium Digital Doorlock C200



C200B2



C200B3



Smart Feature! Easy Function! Digital Doorlock C200 Design



Smart touch

- Sensible LED Blue Lighting
- High Sensitive Touch Pad



Strong Durability

- Diecasting Material
- Front One-Piece Touch Screen




Fire Detection

- Fireproof Structure Design
- High Temperature Alarm System



Smart Function

- Passcode Hide Feature
- One-Touch Anti-Panic



More Smart! More Safe! Simple & Dynamic Design!


LOCpro

Specification



• C200B2 (2 Way)

Type	Electronic (Passcode, RF Tag)
Weight	2.2kg (Including package)
Operating Temperature	-20°C ~ 60°C
Dimension	Outbody 74(W) x 290(H) x 23(D) Inbody 74(W) x 290(H) x 29(D)
Emergency Battery	Alkaline 9V, 6LF22(Optional)



• C200B3 (3 Way)

Type	Electronic & Mechanical (Passcode, RF Tag, Key)
Weight	2.2kg (Including package)
Operating Temperature	-20°C ~ 60°C
Dimension	Outbody 74(W) x 290(H) x 23(D) Inbody 74(W) x 290(H) x 29(D)
Emergency Battery	Alkaline 9V, 6LF22(Optional)

Features



Fireproof Feature

C200 passes the fire-proof test over 1000°C.



Intrusion Alarm Function

It rings the alarm when the door is forcibly opened from outside.



Prank Prevention Function

Incorrectly entering the passcode the five times or more, the doorlock does not operate for 30 seconds.



System Reset Function

It initializes the system and removes all information.



Passcode Hide Function

Use the fake number and the actual passcode together whenever there is any chance of exposing the passcode to others.



Anti-Panic of One-touch way

In the event of an emergency, such as a fire, the anti-panic feature enables residents a quick and safe evacuation by pushing the handle down.



Smart Touch Pad

With the sensible LED and high-quality touch screen, the key pad cover can be utilized easily without having to open it. Every time the user touch the key, it blinks.



Durability of Strong Material

Considering durability and safety the best, it uses the Diecasting material resistant to fire or physical force.



Fire Detection Function

In case of sensing high temperature over 60°C, it alarms and activates door-open function.



Prevention of electronic shock & static

To prevent illegal entrance using the electric & electronic shock, the superior circuit blocks the impact.

LOCpro

FRONTIETEK HOLDINGS CO., LTD

405 Daeryung Techno Town 5th 632 Seobusaet-Gil,
Geumchon-Gu, Seoul, Korea

www.KLOC.co.kr