

# Smart Function ! Easy open ! Simple & Dynamic Design !

# Smart touch

Sensible LED Blue Lighting

High Sensitive Touch Pad

# **Game** Fire Detection

- Fireproof Structure Design
- High Temperature Alarm System



- Diecasting Material
- Front One Piece Touch Screen

# Smart Function

- Passcode Hide Feature
- One -Touch Anti Panic







# More Smart! More Safe! Simple & Dynamic Design!

# LOCPTO

# Specification







#### **Fire Detection Function**

In case of sensing high temperature over 60 , it clarms and activates door-open function.

### **Prank Prevention Function**

Incorrectly entering the passcode the five times or more, the doorlock does not operate for 3 minutes.



## Easy installation without additional hole. Not necessary to drill additional hole. Install doorlock just using by existing hole on the door



## **Passcode Hide Function**

Use the fake number and the actual passcode together whenever there is any chance of exposing the passcode to others.

Door Open by Wireless Connect (Option) Locpro Doorlock can connect home network system to control the door.

## K200B2

Туре	2way : Passcode, RF Tag
Weight	1.7kg (Including package)
Operating Temperature	-20°C~60°C
Dimension	Outbody 79.8(W) x 249.8(H) x 26(D) Inbody 82.2(W) x 249.2(H) x 30(D)
Emergency Battery	Alkaline 9V, 6LF22(Option)
Color	Chrome Silver

## K200B3

Туре	3way:Passcode,RF Tag & Mechanical Key
Weight	1.7kg (Including package)
Operating Temperature	⊆ -20°C ~ 60°C
Dimension	Outbody 79.8(W) x 249.8(H) x 26(D) Inbody 82.2(W) x 249.2(H) x 30(D)
Emergency Battery	Alkaline 9V, 6LF22(Option)
Color	Chrome Silver



### Anti-Panic of One-touch way

In the event of an emergency, such as a fire, the anti-panic feature enables residents a quick and safe evacuation by pushing the handle down.

## **Smart Touch Pad**

With the sensible LED and high-quality touch screen, the key pad cover can be utilized easily without having to open it, Every time the user touch the key, it blinks.





### **Fire Detection Function**

**Durability of Strong Material** 

In case of sensing high temperature over 60 , it 'clarms and activates door-open function.

Considering durability and safety the best, it uses the Diecasting material resistant to fire or physical force.



Prevention of electronic shock & static

To prevent illegal entrance using the electric & electronic shock, the superior circuit blocks the impact.

# ιοςριο

## **FRONTIETEK HOLDINGS CO., LTD**

405 Daeryung Techno Town 5<sup>th</sup> 632 Seoubusaet-Gil, Geumchon-Gu, Seoul, Korea

www.KLOC.co.kr