

# Smart Feature! Easy Fuction!



- Intrusion Alarm
- Electronic Shock & Static Proof

# Easy Convenience

- Open/Close from Inside
- One Time Mode & User Mode



- Wide Keypad
- Comfortable Button
- Smart Function
  - Etiqutte Mode









# More Smart! More Safe!

## Simple & Dynamic Design

# госьго

## Specification & Features



#### L50N Series

Туре	1Way (Passcode only)
Weight	360g (Including package)
Operating Temperature	−20°C ~ 60°C
Dimension	Outbody 60(W) x 121(H) x 21(D) Inbody 66(W) x 130(H) x 27(D)
Emergency Battery	Alkaline 9V, 6LF22(Option)



#### L50K Series

Туре	2Way (Passcode, i-Key)
Weight	360g (Including package)
Operating Temperature	-20°C ~ 60°C
Dimension	Outbody 60(W) $\times$ 121(H) $\times$ 21(D) Inbody 66(W) $\times$ 130(H) $\times$ 27(D)
Emergency Battery	Alkaline 9V, 6LF22(Option)



#### L50S Series

Туре	2Way (Passcode, RF Tag)
Weight	360g (Including package)
Operating Temperature	-20℃ ~ 60℃
Dimension	Outbody 60(W) x 121(H) x 21(D) Inbody 66(W) x 130(H) x 27(D)
Emergency Battery	Alkaline 9V, 6LF22(Option)



#### Intrusion Alarm Function It rings the alarm when the door is forcibly

opened from outside.



# Prank Prevention Function

Incorrectly entering the passcode the tive times or more, the doorlock does not operate for 30 seconds.



#### Master Passcode / RF Tag Function If you set this function, someone can not manipulate the locker lock.



#### Open/Close from Inside

In case that someone's locked in Cabinet by mistake or accident, he or she can open the door from inside by pushing open/close button.



#### One Time Mode & User Mode

According to business model, you can choose One Time Mode or User Mode.



#### Prevention of electronic shock & static

To prevent illegal entrance using the electric & electronic shock, the superior circuit blocks the impact.

### ιοςριο

**FRONTIETEK HOLDINGS CO., LTD** 405 Daeryung Techno Town 5<sup>th</sup> 632 Seoubusaet-Gil, Geumchon-Gu, Seoul, Korea

www.KLOC.co.kr